

**REGION 6 VIPR PRE-AWARD
FIRE EQUIPMENT INSPECTION CHECKLIST
VEHICLE WITH DRIVER**

COMPANY NAME: _____ **DATE:** _____
(On VIPR Agreement)

EQUIPMENT MAKE: _____ **MODEL:** _____

VIN#: _____ **EQUIPMENT/Unit I.D.** _____

EQUIPMENT REQUIREMENTS – VEHICLE W/DRIVER

- ☐ Pickup, Type 1 – GVWR \geq 8,501 lbs., min. 6 ½ ft. bed length ☐ 2WD ☐ 4WD
- ☐ Pickup, Type 2 – GVWR 6,001 to 8,500 lbs., min. 6 ft. bed length ☐ 2WD ☐ 4WD
- ☐ Pickup, Type 3 – GVWR \leq 6,001 lbs., min. 5 ft. bed length ☐ 2WD ☐ 4WD
- ☐ Stakeside, Type 1 – GVWR \geq 14,001 lbs. ☐ dump/tilt box ☐ lift gate ☐ 2WD ☐ 4WD
- ☐ Stakeside, Type 2 – GVWR \geq 10,001 to 14,000 lbs. ☐ dump/tilt box ☐ lift gate ☐ 2WD ☐ 4WD
- ☐ Sport Utility Vehicle: (min. 5 passenger) ☐ 2WD ☐ 4WD ☐ > 6 passengers
- ☐ Passenger Van: 7 to 9 passenger. ☐ 2WD ☐ 4WD

*NOTE: Passenger or passenger-carrying capacity minimums stated above includes the driver.
Vans larger than 9 passengers will not be awarded an agreement.*

Minimum Requirements

		Yes	No
1	VIN # on Equipment matches VIPR		
2	OF-296 Vehicle/Heavy Equipment Safety Inspection completed		
3	Vehicles with GVWR 10,001 lbs. or greater: Annual DOT inspection or Commercial Vehicle Safety Alliance Inspection (49 CFR 396.23) (D.2.2)		
4	The full bed of the truck available for incident use (D.2.1.1)		
5	Vehicles configured to the manufacturers original specifications (D.2.1.1) *lift kits, aftermarket exhaust (i.e., glass packs) and other such modifications that would compromise the integrity of the vehicle are not allowed.		
6	Spare Tire, wheel wrench, jack (D.2.1.1)		
7	Fire Extinguisher: 2A 10BC (D.2.1.1)		
8	STAKESIDES: Flatbed truck with railings that are, at a minimum, the same height of the cab and firmly attached on all 4 sides. The railing on the sides and the rear of the bed must be removable for loading/unloading cargo. (D.2.1.1)		

REMARKS: